



Base station wind power source is not displayed

Data Display Issues: If the display unit is not showing data as expected, perform a factory reset, and reconfigure it. Make sure the power source is stable and the unit is within the ...

If the anemometer arm cannot be mounted pointing to true north, use this procedure to correct the wind direction console reading. Check the current direction of the wind vane on the anemometer.

If you still do not see wind and/or temperature, please try a factory restart on the station. Hold the ALERTS and RAIN buttons together for 5 seconds or until the station resets.

Is the problem that all your weather data, which used to be displayed on a Vantage Vue or Vantage Pro console is no longer displayed there? If so, make sure the console has fresh ...

Following is a basic restart procedure for clocks and weather stations that do not have wind or rain: Bring both units inside and have the units 3-5 feet apart with nothing between them.

If the LED on the unit base does not light up at all, there may be a low battery problem. Make sure your device is switched on and place it outdoors with solar panels facing the sun.

I have my wind sensor set up on a pole on the roof of the house and went up today to change the batteries before winter sets in. The wind sensor was registered with the base station just ...

The Hub (indoor base station) connects to a 2.4GHz home WiFi network, but a mobile hotspot could work. We don't recommend using the Tempest without a WiFi connection.

Make sure the batteries are fresh and are inserted correctly. Unplug the display and wait 10 seconds before plugging it back in again. This can help reset any errors that may be occurring ...

Remove the batteries and/or power adapter from the display unit. Change the A-B-C switch on both units to a new, matching channel then press and hold the reset button for 20 seconds if applicable. ...



Base station wind power source is not displayed

Web: <https://klconsulting.co.za>

